

D135 CONTACTLESS mPOS



Fashion & Retail

Micro & Small Merchants

Food & Beverage







Powered by Monitor



PCI 5 SRED



Pin on Mobile



www.pax.us

SPECIFICATIONS

00	Operating System	Monitor
₿	Processor	Cortex M3
	Memory	Built-in 1MB FLASH + 128KB SRAM External 4MB SPI Nor Flash for Fonts, Config Files
	Card Readers	Chip & PIN NFC Contactless Magnetic Stripe (optional)
((†))	Comms Configurations	Bluetooth®4.2, Supports : Bluetooth® Low Energy 1 Type-C Optional Pogo PIN
4	Battery	250mAh Optional 400mAh
E	Keys / Buttons	1 Button: Power On / Power Off / Sleep / Pair to Bluetooth ® COTS
Ĥ	Indicators	4 RF Indicators, 1 Power Indicators (green & red)
	Cable	1 USB Cable
ふシ	Audio	1 Buzzer
	Ports	1 Type-C OTG POGO PIN (optional)
	Physical	13 x 67 x 67 mm, 63.6g (with MSR)
Ç	Environmental	-10°C ~ 50°C (14°F ~ 122°F) Operating Temperature -20°C ~ 70°C (-4°F ~ 158°F) Storage Temperature 10%-93% Relative Humidity, Non-Condensing
\bigcirc	Certifications	PCI PTS 5.x SRED EMV L1 & L2 EMV CL L1 Mastercard contactless L2 Visa payWave L2 DPAS L2 QUICS L2 AMEX L2 InteacFlash L2 TQM UL FCC IC RoHs



This document is provided to you for informational purposes only. All features and specifications are subject to change without notice. The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by PAX Technology, Inc. is under license. EMV® is a registered trademark in the U.S. and other countries and an unregistered trademark elsewhere. The EMV trademark is owned by EMVCO, LLC. Android™ is a trademark of Google LLC. PAX, PAXBiz®, PAXSTORE, and/or other PAX products referenced herein are either trademarks or registered trademarks of PAX Technology, Inc. or its Affiliates. Other trademarks and trade names are those of their respective owners. © 2022 PAX Technology, Inc. All rights reserved.

